



Aachen, den 30.11.2010

PRODIS-GUT License

to use the label of

Gemeinschaft umweltfreundlicher Teppichboden e.V.

in combination with the label of the related product information system,

GUT-PRODIS-Label

for the article: QUARTZ AB

of the manufctorer: Balta Industries NV/Division ITC

PRODIS-GUT license number: 6F3A3864

Basic product description:

Type of manufacture:	pile carpet acc. EN 1307 - tufted
Type of surface:	loop pile - loop pile like - multicoloured plain
	100% PA6
Type of backing:	textile backing - woven - man-made fibres

The above article fulfills the GUT requirements (compliance with thresholds and ban of use regarding VOC emissions, harmful substances and odor) as well as the declared use characteristics in the pictograms. On behalf of "Gemeinschaft umweltfreundlicher Teppichboden e.V." the license is granted.

Information about the current validity of the license as well as information on the GUT criteria, use and additional characteristics, or related Environmental Product Declarations (EPD), can be found on the related product page at www.gut-ev.de or www.pro-dis.info. Please search with the indicated PRODIS-GUT license number or simply scan the QR code, directly linked with the appropriate product page.



PRODIS

his license was issued electronically and requires no further signature

Gemeinschaft umweittreundlicher Teppichboden e. D-52068 Aachen. Schönebergstrasse 2



THE COMPREHENSIVE EUROPEAN PRODUCT INFORMATION SYSTEM FOR TEXTILE FLOORCOVERINGS

GUT Product Test Criteria and limit values

The GUT Signet can be granted only to members of Gemeinschaft umweltfreundlicher Teppichboden e.V. (Only manufacturers of textile floorcoverings can become members)

The use of the substances listed below is either forbidden or GUT has specified limit values for the substances that must not be exceeded.

ORGANIC CARRIERS (DYEING ACCELERANTS)

There is a ban on the use of the carriers listed.

Di-, tri-, tetra-, penta- and hexachlorobenzenes; di-, tri-, tetra- and pentachlorotoluenes

AZODYES

There is a ban on the use of dyes and pigments which, under reductive conditions, release carcinogenic amines.

4-aminodiphenyl, benzidine, 4-chloro-o-toluidine, 2-naphthylamine, o-amino-azotoluene, 2-amino-4-nitrotoluene, p-chloroaniline, 2,4-diaminoanisol, 4,4'-diaminodiphenylmethane, 3,3'-dichlorobenzidine, 3,3'-dimethoxybenzidine, 3,3'-dimethylbenzidine, 3,3'-dimethyl-4,4'-diaminodiphenylmethane, p-cresidine, 4,4'-methylene-bis-(2-chloroaniline), 4,4'-oxydianiline, 4,4'-thiodianiline, o-toluidine, 2,4-diaminotoluene, 2,4,5-trimethylaniline, o-anisidine, p-amino-azobenzene*, 2,4-xylidine, 2,6-xylidine, 6-amino-2-ethoxynaphthaline**, 4-amino-3-fluorophenol** (*not identifiable, **special procedure required)

DISPERSE DYES

There is a ban on the use of the dyes listed, which are classified as "allergising".

C.I. Disperse Blue 1, -3, -7, -26, -35, -102, -106 and -124, C.I. Disperse Orange 1, -3, -37/76, C.I. Disperse Red 1, -11 and -17, C.I. Disperse Yellow 1, -3, -9, -39 and -49

CARCINOGENIC DYES

There is a ban on the use of the dyes listed, which are classified as "carcinogenic".

C.I. Acid Red 26, C.I. Basic Red 9, C.I. Direct Red 28, C.I. Direct Blue 6, C.I. Disperse Blue 1, C.I. Disperse Yellow 3, C.I. Direct Black 38

HEAVY METALS

Dyes and pigments containing the listed heavy metals as ingredients of the dyeing component must not be used to dye the pile material. The limit value for the total heavy metal content of a fitted carpet is 100 mg/kg.

Pb (lead), Cd (cadmium), Hg (mercury), Cr (chromium total) or Cr(VI)

FLAME RETARDANTS

There is a ban on the use of the halogenous and phosphorous flame retardants listed.

PBB, TRIS, TEPA, SCCPs, PeBDE (pentabromodiphenylether)

GUT test procedure No. 3

GUT test procedure No. 1

GUT test procedure No. 2

TAPIJT GETEST VOOR EEN BETER LEEFMILIEU

CARPETS TESTED FOR A BETTER LIVING ENVIRONMENT CONTAMINANT-TESTED 3EMEINSCHAFT UMWELTFREUNDLICHER TEPPICHBODEN MOQUETTES TESTÉES POUR LA QUALITÉ DE VOTRE ENVIRONNEMENT TESTÉE SUR LA PRÉSENCE DE SUBSTANCES NOCIVES **TEPPICHBODEN SCHADSTOFFGEPRÜFT** 2 D-52068 AACHEN GETEST OP SCHADELIKE STOFFEN

GUT test procedure No. 6

GUT test procedure No. 4

GUT test procedure No. 5

ACTIVE BIOCIDAL SUBSTANCES

For the biocides listed that may be contained as active substances in respective formulations there is either a ban on their use or a limit value was specified for the respective active substance or group of active substances.

- 1) There is a ban on the use of products containing **TBT**.
- 2) The limit value for the **chlorophenols**, pentachlorophenol and tetrachlorophenol (PCP and TeCP), is 0.1 mg/kg.
- 3) For **orthophenylphenol** (OPP), there is a limit value of 1 mg/kg.
- For the **chlororganic pesticides** listed, there is a limit value of 0.04 mg/kg for each individual substance and of 1 mg/kg for the sum of all components, respectively.
 o,p' and p,p' –DDE, –DDD and –DDT, α, β, δ, ε-hexachlorocyclohexane, aldrine, dieldrine, endrine, heptachlor,

heptachloroepoxide, hexachlorobenzene, lindane, methoxychlor, mirex, toxaphene, * α -and , β -endosulphane

- 5) For the **phosphororganic pesticides** listed, there is a limit value of 0.04 mg/kg for each individual substance and of 1 mg/kg for the sum of all components, respectively. Diazinon, dichlorofenthion, dichlorophos**, malathion**, parathion-ethyl, parathion-methyl*, trifluralin (*special procedures required, **other identification limits).
- 6) For the **herbicides**, 2,4,5-T and 2,4-D, there is a limit value of 0.04 mg/kg for each individual substance and of 1 mg/kg for the sum of all components, respectively.
- 7) Except for permethrine, there is a ban on the use of all **pyrethroids** for the protection of wool against moths and beetles.
- 8) As moth- and beetle-proofing agent for the sole finishing of woollen fitted carpets, **permethrine** may be used up to a maximum limit of 210 mg/kg. Application must be conducted in compliance with a prescribed procedure.

EMISSIONS FROM TEXTILE FLOORCOVERINGS

Volatile organic components from textile floorcoverings are determined in compliance with the test-chamber process. The following limit values are specified for the components listed.

TVOC	300 µg/m³	
VOC without LCI	100 µg/m³	Test chamber method (EN 13419; 1+2; ISO 16000). The test is performed 72h
R-Value	≤]	after $t = 0$. For calculation and evaluation
SVOC (C_{16} to C_{22})	30 µg/m³	of the R-value, the actual LCI-Value List as published by AgBB* is used.
Cancerogenic Substances (EU-list Class 1 a. 2)	n.n.	

* Ausschuss zur gesundheitlichen Bewertung von Baumaterialien

ODOUR

GUT test procedure No. 9

GUT test procedure No. 10

The material tested should only have the low-intensity odour typical of a new product.

The test mark following appraisal by a team of 7 persons must be a value < 4.

REQUIREMENTS ON LATICES

The latices used for coating must meet the following requirements on the residual monomer content.

For the individual substances styrene and 4-PCH, the limit value is 200 mg/kg of latex, and for ethylbenzene and 4-VCH, the limit value for each is 50 mg/kg of latex.

The limit value of the sum for all 4 components is 400 mg/kg of latex.

For the manufacture of foam coatings, there is a ban on the use of the vulcanisation accelerator Zn-diethyldithiocarbamate (ZDEC).

GUT test procedure No. 8

DECLARATION OF PERFORMANC

DOP: 1011#IE0ACV

1. Unique identification code of the product-type:

1011#IE0ACV

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

QUARTZ AB - Textiler Bodenbelag - pile carpet acc. EN 1307

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specifi- cation, as foreseen by the manufacturer:

For use as floor covering in buildings (see EN 14041) according to the manufacturer's specifications.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Balta Industries NV/Division ITC - Kanegemstraat - B - 8700 Tielt

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

- - -

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

 In case of the declaration of performance concerning a construction product covered by a harmonised standard: Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).

Notified Body

not required

certificate of constancy of performance

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

- not applicable
- 9. Declared performance

Performance	Harmonised technical specification
Circa 1	EN 14041 :2004/AC:2006
Ê DL PCP	EN 14041 :2004/AC:200
NA HCHO	EN 14041 :2004/AC:200
1965 DS	EN 14041 :2004/AC:200
NPD	EN 14041 :2004/AC:200
NPD	EN 14041 :2004/AC:200
· 72	EN 14041 :2004/AC:200
0.05	EN 14041 :2004/AC:200
NPD	EN 14041 :2004/AC:200
	DL PCP NA HCHO NPD NPD 0.05

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4 Signed for and on behalf of the manufacturer by:

> Luc Nelis, Production Manager (name and function)

08.07.2013, Tielt (place and date of issue)

(signature



Dhr. Luc Nelis BALTA INDUSTRIES NV - AFDELING ITC Kanegemstraat 15 8700 TIELT

Your notice of	Your reference	our reference	date
		PW/357	2012-02-14

Certification Report Nr. 12/357 Modification of certification report 10/10239 dd. 2010-11-16

1. Description of the flooring:

Product group:	Tufted broadloom carpet
	100% polyamide
	woven textile backing
Total mass:	1200 g/m ² - 2470 g/m ²
Effective pile thickness:	2.0 mm - 14.0 mm

2. Executed tests:

European Fire classification in accordance with EN 13501-1 (2002)		
Class	EN ISO 11925-2 (15 s surface flame attack) or EN 14041 (2004)	EN ISO 9239-1 (test duration = 30 min)
$C_{\rm fl}$	E _{fl}	heat flux \geq 4,5 kW/m ²

3. Conclusion:

Referring to the means of control and the test results, the before mentioned product group can be classified as follows:

glued on a non-combustible substrate*

* End use substrates of classes A1or A2-s1,d0 (ISO 13238:2010 § 5.2.2)

This certification report runs to 2 pages and may be reproduced, as long as it is presented in its entire form, without written permission of Centexbel.

The results of the analysis cover the received samples. Centexbel is not responsible for the representativeness of the samples.

Centexbel is recognized as notified body 0493 for the European Construction Products directive and the European directive for personal protective equipment

and European unceuve for p	cisonai protecuve equipment
CENTEXBEL GENT	CENTEXBEL BRUSSELS
Technologiepark 7	Montoyerstraat 24-B2
BE-9052 Zwijnaarde (Gent)	BE-1000 Brussels
Tel. +32 9 220 41 51	Tel. +32 2 287 08 30
Fax +32 9 220 49 55	Fax +32 2 230 68 15
e-mail gent@centexbel.be	e-mail brussel@centexbel.be

CENTEXBEL VERVIERS Avenue du Parc 38 BE-4650 Herve (Chaineux) Tel. +32 87 32 24 30 Fax +32 87 34 05 18 e-mail chaineux@centexbel.be

VAT BE 0459 218 289 - Fin. Acc. 210-0472965-45 - IBAN BE44 2100 4729 6545



Addressee	
Balta Industries nv - afdeling ITC	

our ref. PW/357 date 2012-02-14 page number 2

Certification Report Nr. 12/357

Related commercial names to this product group are:

related commercial names to any product group are.			
IR+dessin AB			
MONTEVERDI AB			
OLYMPIC AB			
OPTIMA AB / CARESSE AB			
PALM BEACH AB			
PARMA AB			
PA+dessin AB			
PLATINUM AB			
PRECIOSA AB			
QUARTIER AB			
QUARTZ AB			
QUARTZ NEW AB			
REKORD AB			
RIVOLI AB			
ROSSINI AB			
ROXANE AB			
SAPORO AB			
SEDUCTION AB			
SERENADE AB			
SHERWOOD AB			
SPONTINI AB			
SPRINGDALE TWIST AB			
SPUMANTE AB			
SUPREME TOUCH AB			
SYMPHONY AB			
TITAN AB / CHAMPION AB			

The obtained classification is based on the next test reports:

Centexbel: 65089 of 2008-10-22 Centexbel: 66103 of 2009-01-14 Centexbel: 67117 of 2009-03-06 Centexbel: 67118 of 2009-03-06 Centexbel: 68414/E of 2009-05-06 Centexbel: 68414/I of 2009-05-06 Centexbel: 76368 of 2010-11-02 Centexbel: 81137 of 2011-08-24 Centexbel: 11.82629.01 of 2011-12-16 Centexbel: 11.82630.01 of 2011-12-16

Certificate valid until 2016-08-24

Petra Wittevronger product certifier



HOMOLOGATION

HOMOLOGATION UPEC MOQUETTES TOUFFETEES ET TISSEES EN LES

Attestation n° 10/278

- La Société BALTA Industries nv Division ITC Kanegemstraat 15 B 8700 Tielt
- Usine de Tielt (BE)

est autorisée à utiliser l'homologation moquettes touffetées et tissées en lés, pour le produit

QUARTZ AB

Les caractéristiques du produit homologué figurent en page 2.

Le classement UPEC associé est : U3 P3 E1 C0

La présente attestation est valable à compter du 02/12/2010.

Cette attestation comporte 2 pages.

Correspondant : Danielle COUTANT Tél. : 01 64 68 83 96 Fax : 01 64 68 84 76 E-mail : danielle.coutant@cstb.fr

Direction Technique La Charles BALOCHE

Sauf annulation, suspension ou modification, cette attestation est valide.

La liste des produits homologués est tenue à jour au CSTB et disponible sur le site Internet www.cstb.fr.

CENTRE SCIENTIFIQUE ET TECHNIQUE DU BATIMENT SIÈGE SOCIAL > 84 AVENUE JEAN JAURÈS | CHAMPS-SUR-MARNE | 77447 MARNE-LA-VALLÉE CEDEX 2 TÉL. (33) 01 64 68 82 82 | FAX. (33) 01 60 05 70 37 | www.cstb.fr MARNE-LA-VALLÉE | PARIS | GRENOBLE | NANTES | SOPHIA-ANTIPOLIS



HOMOLOGATION UPEC MOQUETTES TOUFFETEES ET TISSEES EN LES

Attestation n° 10/278

QUARTZ AB

FABRICANT	BALTA INDUSTRIES NV DIVISION ITC
DISTRIBUTEUR	BALTA INDUSTRIES NV DIVISION ITC
CLASSEMENT UPEC	U3 P3 E1 C0
CLASSE DE CONFORT	LC1
Présentation :	
largeur des lés (m)	4 & 5
Caractéristiques :	4000
Masse surfacique totale (g/m²)	1800
Epaisseur totale (mm)	5,5
Jauge de la machine	1/10"
Nbre de points au dm (sens transversal)	39,4
Nbre de points au dm (sens longitudinal)	56
Velours :	
Туре	bouclé uniforme
Colorio	
Coloris	chinés
Nature	100% polyamide
Epaisseur utile (mm)	2,6
Masse volumique (g/cm ³)	0,115
Masse surfacique utile (g/m²)	300
Solidité des coloris :	
Lumière	≥5
frottement à sec	
	≥4
frottement humide	≥4
Dossier :	
Туре	tissé
Nature	polypropylène
Masse surfacique (g/m²)	100
Enduction :	
Nature	SBR
Masse surfacique (g/m²)	1140
Sous-couche :	
Туре	tissé
Nature	polypropylène
Masse surfacique (g/m ²)	70
Masse volumique (g/cm ³)	-
Epaisseur apparente (mm)	-
Pose :	
Mode de pose	collée
Types de colles préconisées	
	résines synthétiques (polyacrylique) en émulsion

CENTRE SCIENTIFIQUE ET TECHNIQUE DU BATIMENT SIÈGE SOCIAL > 84 AVENUE JEAN JAURÈS | CHAMPS-SUR-MARNE | 77447 MARNE-LA-VALLÉE CEDEX 2 TÉL. (33) 01 64 68 82 82 | FAX. (33) 01 60 05 70 37 | www.cstb.fr MARNE-LA-VALLÉE | PARIS | GRENOBLE | NANTES | SOPHIA-ANTIPOLIS



ZERTIFIKAT

Genehmigung zur Nutzung des Prüfzeichens

MATERIALPRÜFUNG AUF ALLERGIKER-EIGNUNG

Die

TÜV NORD Systems GmbH & Co. KG, Hamburg,

bestätigt, dass ausgewählte Artikel*) der Teppichboden-Produktgruppen

- Polyamid,
- Polyamid/Polypropylen und
- Polypropylen

die von der TÜV NORD Systems GmbH & Co. KG gestellten Anforderungen erfüllen.

Der

BALTA INDUSTRIES NV, Sint-Baafs-Vijve (Belgien),

wird daher das Recht verliehen, das nachstehende Prüfzeichen im Zusammenhang mit den ausgewählten Artikeln der o. a. Teppichboden-Produktgruppen zu führen.

*) siehe Rückseite

TÜV NORD Systems GmbH & Co. KG Prüfstelle für Raumlufthygiene

Dipl.-Ing. M. Klein Essen, 07. Oktober 2011





Für die nachfolgend aufgeführten Teppichboden-Artikel wurde der BALTA INDUSTRIES NV, Sint-Baafs-Vijve (Belgien) vom TÜV NORD, Hamburg, die Genehmigung erteilt, das TÜV NORD Prüfzeichen "Teppichboden aus allergenkontrolliertem Material – Für Allergiker geeignet" zu führen:

Teppichboden-Produktgruppe "Polyamid"

Chic UX, Elite UX, City Life UX, Angelo UX, Akzento TR, Chambord UX, Corsa UX, Figaro New UX, Forta TR, Parma V, Parma TR, Perugia UX, Preciosa UX, Preciosa TR, Richelieu TR, Sublimo UX, Rivoli TR, Altona UX, Corsa TR, Roxane UX, Quartier TR, Quartz TR, Rossini TR, Saphir TR, Henley Twist New TR, Elite TR, Ambiente UX, Harmony UX, Serenade UX, Linares UX, Yaris UX, Aktua UX, Namibia UX, Bellagio WT, Gerona WT, Apollo TR, Fortesse TR, Master TR, Mustang TR, Optima TR, Champion TR, Podium TR, Victory TR, Olympic TR, Platinum TR, Spontini TR, Cavalli TR, Altro TR, Prominent TR, Projecta TR, PJ + Name TR, Progressa TR, PG + Name TR, Promenade TR, PM + Name TR, Exclusivo WFB

Teppichboden-Produktgruppe "Polyamid / Polypropylen"

Coral UX, Star UX, Star TR, Forum UX, Robust UX, Tessuto UX, Tampa UTQ+, Tampa TR, Desert Twist TR, Desert Twist TF, Reggae TF, Tweed TR

Teppichboden-Produktgruppe "Polypropylen"

Casadesign UTQ+, Natura, Velvet Twist TF, Capitol Cable & Cord TF, Solid TR, Lounge TF, Stainsafe Heathers TR, Pure, Curly TF, Focus TF, Rasta TF, Shepherd Twist TR, Stainsafe Favourite Premium TR, Stainsafe Favourite Elite TR, Stainsafe Touch TR, Mistral TF, Passat TF, Scirocco TF, Scala TF, Scala Design TF, Salzburg TF, Sensations TR, Giro Gala TR, Giro Gala UTQ+