

## Dynamic GT LV

Manufacturing process	Needlefelt	ISO 2424						
Type of surface	Flecked							
Surface aspect	Flat	ISO 2424						
Backing	LV	ISO 2424						
Pile yarn composition	100% dorix® PA							
Pile weight	650 g/m <sup>2</sup>							
Total weight	1430 g/m <sup>2</sup>	+/- 10% ISO 8543						
Total height	6,5 mm	+/- 10% ISO 1765						
Overall use class	Commercial 33, Areas with heavy use	EN 1307						
Luxury class	LC1	EN 1307						
Castor chair suitability	Yes, permanent use	EN 985						
Stair suitability	Yes, permanent use	EN 1307						
Colour fastness to light	≥ 5	ISO 105-B02						
Colour fastness to rubbing, wet and dry	≥ 4	ISO 105-X12						
Colour fastness to water	≥ 4	ISO 105-E01						
Dimensional stability	Shrinkage ≤ 1,2 %	ISO 2551						
	Extension ≤ 0,5 %	ISO 2551						
Electrostatic charging	< 2kV	ISO 6356						
Vertical resistance	< 1,0x10 <sup>8</sup> Ω	ISO 10965						
Horizontal resistance	< 1,0x10 <sup>8</sup> Ω	ISO 10965						
Impact sound protection ΔLW	20 dB	ISO 717-2						
Acoustical sound absorption αS	Hz	125	250	500	1000	2000	4000	ISO 354
	αW	0,01	0,07	0,09	0,20	0,41	0,65	
Evaluated sound absorptions grade αW	0,20	ISO 11654						
Thermal resistance	0,10 m <sup>2</sup> .K/W	ISO 8302						
Slip resistance	> 0,3	Machine direction	EN 13893					
	> 0,3	Crossdirection	EN 13893					
Flammability	Bfl,s1 (Glued)	EN 13501-1						
Prodis-ID (GuT)	2BB3E65A	www.pro-dis.info						
AbZ Nr.	Z-156.601-697							
Health and environment mark RAL-UZ 128	Contract nr.: 23641							
TÜV PROFICERT product	Certificate number: 70 710 5617-2							

## Floorsymbols



## Certificates

EN 14041



Slip resistance:  
DS

DOP:  
1061#186LV00  
Textile Floorcovering  
EN1307





www.blauer-engel.de/uz128





70 710 5617-2  
www.proficert.com



tested for: emissions  
harmful substances  
**PREMIUM**

2018-05-03

Vebe Floorcoverings b.v. products are to be installed in full accordance with Vebe installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. Vebe products should only be used as floorcoverings. Note: Vebe Floorcoverings b.v. reserves the right to adapt this specification without giving prior notice. For the latest versions of the technical specifications, check our internet site.

In the area of office chairs we recommend to use mats made of polycarbonate. This extends the life of your carpet.

Laying: Fully glued with adhesive that withstands chair castors.

The producer reserves the right to change technical specifications. Due to variations in raw materials and production circumstances, the product may vary from batch to

batch.