


Stone GT LV

Manufacturing process	Needlefelt	ISO 2424														
Surface aspect	Flat	ISO 2424														
Width	200 cm, 400 cm															
Backing	LV	ISO 2424														
Pile yarn composition	70% PA / 30% PP															
Pile weight	600 g/m ²															
Total weight	1010 g/m ²	+/- 10% ISO 8543														
Total height	5.2 mm	+/- 10% ISO 1765														
Overall use class	Commercial 33, Areas with heavy use	EN 1307														
Luxury class	LC1	EN 1307														
Castor chair suitability	Yes, permanent use	EN 985														
Stair suitability	Yes, permanent use	EN 1307														
Colour fastness to light	≥ 5	ISO 105-B02														
Colour fastness to rubbing, wet and dry	≥ 4	ISO 105-X12														
Colour fastness to water	≥ 4	ISO 105-E01														
Colour fastness to soiling	≥ 3	EN 1269														
Dimensional stability	Shrinkage ≤ 1,2 % Extension ≤ 0,5 %	ISO 2551 ISO 2551														
Electrostatic charging	< 2kV	ISO 6356														
Vertical resistance	< 1,0x10 ⁸ Ω	ISO 10965														
Horizontal resistance	< 1,0x10 ⁸ Ω	ISO 10965														
Impact sound protection ΔLW	20 dB	ISO 717-2														
Acoustical sound absorption αS	<table border="1"> <thead> <tr> <th>Hz</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td>αW</td> <td>0.03</td> <td>0.06</td> <td>0.09</td> <td>0.17</td> <td>0.26</td> <td>0.42</td> </tr> </tbody> </table>	Hz	125	250	500	1000	2000	4000	αW	0.03	0.06	0.09	0.17	0.26	0.42	ISO 354
Hz	125	250	500	1000	2000	4000										
αW	0.03	0.06	0.09	0.17	0.26	0.42										
Thermal resistance	0.09 m ² .K/W	ISO 8302														
Slip resistance	> 0,3 Machine direction > 0,3 Crossdirection	EN 13893 EN 13893														
Flammability	Bfl,s1 (Glued)	EN 13501-1														
Prodis-ID (GuT)	CEFF2141	www.pro-dis.info														
AbZ Nr.	Z-156.601-697															
Health and environment mark RAL-UZ 128	Contract nr.: 23641															

Floorsymbols



Certificates



www.blauer-engel.de/uz128

dorix®

Vebe Floorcoverings b.v. products are to be installed in full accordance with Vebe installation instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. Vebe products should only be used as floorcoverings. Note: Vebe Floorcoverings b.v. reserves the right to adapt this specification without giving prior notice. For the latest versions of the technical specifications, check our internet site.

In the area of office chairs we recommend to use mats made of polycarbonate. This extends the life of your carpet.

Laying: Fully glued with adhesive that withstands chair castors.

The producer reserves the right to change technical specifications. Due to variations in raw materials and production circumstances, the product may vary from batch to batch.