


## Strong 738 L

<b>Manufacturing process</b>	Needlefelt		ISO 2424
<b>Type of surface</b>	Flecked		
<b>Surface aspect</b>	Coarse Fibred		ISO 2424
<b>Width</b>	200 cm		
<b>Backing</b>	LV		ISO 2424
<b>Pile yarn composition</b>	65% PP / 35% dorix® PA		
<b>Pile weight</b>	400 g/m <sup>2</sup>		
<b>Total weight</b>	1000 g/m <sup>2</sup>	+/- 10%	ISO 8543
<b>Total height</b>	5.0 mm	+/- 10%	ISO 1765
<b>Overall use class</b>	Commercial 33, Areas with heavy use		EN 1307
<b>Luxury class</b>	LC1		EN 1307
<b>Castor chair suitability</b>	Yes, permanent use		EN 985
<b>Stair suitability</b>	Yes, permanent use		EN 1307
<b>Colour fastness to light</b>	≥ 5		ISO 105-B02
<b>Colour fastness to rubbing, wet and dry</b>	≥ 4		ISO 105-X12
<b>Colour fastness to water</b>	≥ 4		ISO 105-E01
<b>Dimensional stability</b>	Shrinkage ≤ 1,2 % Extension ≤ 0,5 %		ISO 2551 ISO 2551
<b>Electrostatic charging</b>	< 2kV		ISO 6356
<b>Vertical resistance</b>	< 1,0x10 <sup>8</sup> Ω		ISO 10965
<b>Thermal resistance</b>	0.10 m <sup>2</sup> .K/W		ISO 8302
<b>Slip resistance</b>	> 0,3 Machine direction > 0,3 Crossdirection		EN 13893 EN 13893
<b>Flammability</b>	Cfl,s1 (Glued)		EN 13501-1

## Floorsymbols



## Certificates



**dorix®**