





















Technical specifications

Enduro meets the requirements of EN ISO 10582

		Enduro Dryback	Enduro Click
	Total thickness	EN-ISO 24346 2.0 mm	4.0 mm
	Wearlayer thickness	EN-ISO 24340 0.30 mm	0.30 mm
	Collection size	20	20
	Domestic use	EN-ISO 10874 23	23
	Commercial use	EN-ISO 10874 31	31
	Tile size	EN-ISO 24342 30.4 x 60.9 cm	30.5 x 61 cm
	Plank size	EN-ISO 24342 17.7 x 121.9 cm	18.5 x 121.2 cm
	Packaging per carton tiles	4.09 m ² (22 pcs)	2.23 m ² (12 pcs)
	Packaging per carton planks	4.77 m ² (22 pcs)	2.24 m ² (10 pcs)
	Squareness and straightness	EN-ISO 24342 < 400 mm < 0.25 mm > 400 mm < 0.35 mm	< 400 mm < 0.25 mm > 400 mm < 0.35 mm
	Total weight	ISO 23997 ca. 3000 g/m ²	ca. 6700 g/m ²
	Wear layer Binder Content	EN-ISO 10582 Type 1	Type 1
	Slip resistance	DIN 51130 R10	R10
	Acoustical impact noise reduction	EN-ISO 717-2 5 dB	6 dB / 15 dB in combination with Forbo underlay
	Castor chair continuous use	ISO 4918 Good	Good
	Residual indentation	ISO 24343-1 ≤ 0.10 mm	≤ 0.10 mm
	Light fastness	ISO 105-B02 ≥ 6	≥ 6
	VOC emissions reaction to fire	EN-IS 160009 ≤ 100 µg/m ³	≤ 100 µg/m ³
	Resistance to chemicals	ISO 26987 Good	Good
	Dimension stability	EN-ISO 23999 ≤ 0.10%	≤ 0.10%
	Fire resistance	EN 13501 B _f -s1, G, NCS	B _f -s1, L, NCS with and without Forbo underlay
	Slip resistance	EN 13893 DS - µ > 0.30	DS - µ > 0.30
	Thermal conductivity	ISO 8302 0.25 W/mK	0.25 W/mK
	Body voltage	EN 1815 < 2 kV	< 2 kV

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.
All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.
The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites.

